

HARDWARE FEATURES

Interface	1 10/100Mbps WAN/LAN Port 1 Reset Button 1 USB 2.0 Port 1 Mode Switch 1 WPS Button
External Power Supply	5V/2A
Dimensions (W x D x H)	2.91*2.64*0.87 in. (74*67*22mm)
Antenna Type	On-Board
Wireless Standards	IEEE 802.11ac/n/a 5GHz IEEE 802.11b/g/n 2.4GHz
Frequency	2.4GHz and 5GHz
Signal Rate	5GHz: Up to 433Mbps(Only with 11AC Wireless Adapter); Up to 150Mbps with 11N Wireless Adapter 2.4GHz: Up to 300Mbps 11a 54M: -76dBm; 11ac VHT20 MCS8: -70dBm; 11ac VHT40 MCS9: -65.5dBm; 11ac VHT80 MCS9:
Reception Sensitivity	-61.5dBm 2.4GHz: 11g 54M: -76dBm 11n; HT20 MCS7: -74dBm; 11n HT40 MCS7: -71dBm CE:
Transmit Power	<20dBm(2.4GHz) <23dBm(5GHz)
Wireless Functions	Enable/Disable Wireless Radio, WDS Bridge, WMM, Wireless Statistics
Wireless Security	64/128-bit WEP,WPA / WPA2,WPA-PSK/WPA2-PSK encryption
Quality of Service	WMM, Bandwidth Control
Management	Access Control Local Management Remote Management
WAN Connection Type	Dynamic IP/Static IP/PPPoE/ PPTP(Dual Access)/L2TP(Dual Access)
DHCP	Server, Client, DHCP Client List, Address Reservation

HARDWARE FEATURES

Port Forwarding	Virtual Server, Port Triggering, UPnP, DMZ
Dynamic DNS	DynDns, Comexe, NO-IP
VPN Pass-Through	PPTP, L2TP, IPSec
Access Control	Parental Control, Local Management Control, Host List, Access Schedule, Rule Management
Firewall Security	DoS, SPI Firewall, IP Address Filter/Domain Filter, IP and MAC Address Binding
Protocols	Supports IPv4
Guest Network	2.4GHz guest network × 1 5GHz guest network × 1
Certification	CE, FCC, RoHS
Package Contents	AC750 Wireless Travel Router TL-WR902AC Power Adapter RJ45 Ethernet Cable Quick Installation Guide
System Requirements	Windows 10/8.1/8/7/Vista/XP, Mac OS or Linux-based operating system
Environment	Operating Temperature: 0°C~40 °C (32 °F~104°F) Storage Temperature: -40°C~70 °C (-40 °F~158°F) Operating Humidity: 10%~90% non-condensing Storage Humidity: 5%~90% non-condensing